

PLASTIC

GLASS

STONE

WOOD

METAL



EMOTION
TECHNOLOGY



Air cooling



Servo-fan cooling



Compressed air cooling



Liquid cooling

Size

kW max (S6 60%)



RPM max

TOOL

TOOL CHANGE

FEATURES

SBC



142

44

on request

3800

160

57

on request

2400

200

80

2400

Disc

Manual

Heavy cutting processes

SBE



93

11,8

13

on request

4500

107

23,5

25,9

33,2

4500

127

37,5

40

50

3800

Disc

Manual

SBE Design
Easyspin
IP66

SBE.M



93

11,8

13

on request

4500

107

23,5

25,9

33,2

4500

127

37,5

40

50

3800

Disc
G 1/2"

Manual

SBE Design
Easyspin
IP66

SBE.X



107

25,9

33,2

8000 / 10000

127

40

50

6000 / 8000

ISO 40 - HSK

ISO 40/50 - HSK

Automatic / Rapid
Index
Genius**SBE Design**
Ghost water joint
H2O sensor

SE.A



150

5,2

12000

ISO 30 - HSK

Automatic / Rapid

Ghost water joint
H2O sensor

SE.S



170

16,5

8000 / 12000

ISO 40 - HSK

Automatic / Rapid
Index
Genius**Ghost** water joint
H2O sensor

SE.CL



150

19,2

12000

ISO 30/40 - HSK

170

24

8000 / 12000

ISO 40 - HSK

Automatic / Rapid

Ghost water joint
H2O sensor

SL



68

3,6

15000 / 18000 / 24000

89

6,6

14000

104

10,8

10000

Disc
ER25 - ER32
G 1/2" - ISO 40Manual
Genius

High speed

AD



127

14

on request

4500

142

18

17,6

4500

Disc

Manual

Multi cutting
Compact dimensions

SC SM



02

4,4

3600

12

5,9

3600

Baking pad

Manual

Shaft stroke 50mm

Shaft stroke 80mm

